


**21.015.01**
**Winkel 45°**

**HIV**

| d   | Art.-Nr.       | LS | VE  | PN | L   | Z    | E   | kg     |
|-----|----------------|----|-----|----|-----|------|-----|--------|
| 12  | 721.015.01.012 | 1  | 400 | 16 | 12  | 4,0  | 17  | 0,005  |
| 16  | 721.015.01.016 | 1  | 250 | 16 | 14  | 5,0  | 21  | 0,006  |
| 20  | 721.015.01.020 | 1  | 180 | 16 | 16  | 5,5  | 28  | 0,020  |
| 25  | 721.015.01.025 | 1  | 100 | 16 | 19  | 6,0  | 33  | 0,026  |
| 32  | 721.015.01.032 | 1  | 100 | 16 | 22  | 7,5  | 41  | 0,045  |
| 40  | 721.015.01.040 | 1  | 50  | 16 | 26  | 10,5 | 50  | 0,070  |
| 50  | 721.015.01.050 | 1  | 30  | 16 | 31  | 11,5 | 61  | 0,120  |
| 63  | 721.015.01.063 | 1  | 30  | 16 | 38  | 14,0 | 76  | 0,200  |
| 75  | 721.015.01.075 | 1  | 8   | 16 | 44  | 17,0 | 90  | 0,320  |
| 90  | 721.015.01.090 | 1  | 6   | 16 | 51  | 21,5 | 107 | 0,550  |
| 110 | 721.015.01.110 | 1  | 6   | 16 | 61  | 26,0 | 130 | 0,915  |
| 125 | 721.015.01.125 | 1  | 6   | 16 | 69  | 31,0 | 147 | 1,315  |
| 140 | 721.015.01.140 | 1  | 6   | 16 | 76  | 34,0 | 163 | 1,660  |
| 160 | 721.015.01.160 | 1  | 4   | 16 | 86  | 38,0 | 192 | 3,060  |
| 200 | 721.015.01.200 | 1  | 2   | 10 | 108 | 48,0 | 230 | 4,500  |
| 225 | 721.015.01.225 | 1  | 2   | 10 | 121 | 55,0 | 260 | 6,400  |
| 250 | 721.015.01.250 | 1  | 1   | 10 | 131 | 58,0 | 286 | 7,700  |
| 280 | 721.015.01.280 | 1  | 1   | 10 | 146 | 62,0 | 320 | 10,460 |
| 315 | 721.015.01.315 | 1  | 1   | 10 | 164 | 66,0 | 359 | 15,500 |