



21.447.10
2-Wege Kugelhahn VK Dual Block aus PVC-U mit integrierter Halterung, ohne Gewindebuchsen, radial lösbar


Mit gesicherten Überwurfmutter.
 Austauschbare Gewinde und identische Einbaulängen wie Kugelhahn VK.
 Anschluß: Gewindemuffen.
 Dichtwerkstoff: PTFE/EPDM.

VKDFV/EPDM

DN	R	Art.-Nr.	PN	B	B ₁	C	C ₁	E	H	H ₁	L	Z	kg	LS	VE
10	3/8"	121.447.010.016	16	54,0	29,0	67	27	54	103	65	11,4	80,2	0,215	1	22
15	1/2"	121.447.010.020	16	54,0	29,0	67	27	54	110	65	15,0	80,0	0,210	1	22
20	3/4"	121.447.010.025	16	65,0	34,5	85	36	65	116	70	16,3	83,4	0,335	1	12
25	1"	121.447.010.032	16	69,5	39,0	85	36	73	134	78	19,1	95,8	0,448	1	6
32	1 1/4"	121.447.010.040	16	82,5	46,0	108	44	86	153	88	21,4	110,2	0,678	1	4
40	1 1/2"	121.447.010.050	16	89,0	52,0	108	44	98	156	93	21,4	113,2	0,955	1	6
50	2"	121.447.010.063	16	108,0	62,0	134	58	122	186	111	25,7	134,6	1,667	1	3

21.447.10
2-Wege Kugelhahn VK Dual Block aus PVC-U mit integrierter Halterung, radial lösbar


Mit gesicherten Überwurfmutter.
 Anschluß: Gewindemuffen.
 Dichtwerkstoff: PTFE/EPDM.

VKDFV/EPDM

DN	R	Art.-Nr.	PN	B	B ₁	C	C ₁	E	H	H ₁	L	Z	kg	LS	VE
65	2 1/2"	121.447.010.075	16	164	87	327	272	164	235	133	30,2	174,6	4,395	1	
80	3"	121.447.010.090	16	177	105	327	272	203	270	149	33,3	203,4	7,260	1	1
100	4"	121.447.010.110	16	195	129	385	330	238	308	167	39,3	229,4	11,100	1	1